

# DESIGNERS GUILD

## PERFECT EGGSHELL

<b>General</b>	<p>A high quality waterbased acrylic topcoat for wood substrates which is suitable for internal and external use.</p> <p>Formulated to resist moisture, staining and general wear and tear.</p>		
<b>Product Codes</b>	<b>Product</b> Perfect Eggshell	<b>Product code</b> TBC	<b>Sheen</b> 20%
<b>Technical Data</b>	<p>A waterbased acrylic topcoat for use on timber.</p> <p>Suitable for interior (including kitchens and bathrooms) and exterior use.</p> <p>Low odour and environmentally friendly.</p> <p>Excellent coverage properties.</p> <p>Yellowing resistant properties.</p> <p>They offer excellent resistance to mechanical damage.</p>		
<b>VOC Information</b>	<p>Low VOC. This product contains maximum 40grams/litre VOC. The EU limit for this product (Cat A/e): 130g/l</p>		
<b>Application</b>	<p>Stir well before use.</p> <p>Do not use in extremes of temperature. Use between 8°C to 30°C. Do not apply when rain or dew is imminent.</p> <p>These products are formulated for brush, roller application and can be sprayed.</p> <p>When painting on external wooden substrates Designs Guild wood primer and undercoat must be used.</p> <p>When painting on external substrates we recommend a minimum of two coats</p>		
<b>Drying Time</b>	<p>Touch dry: 2 – 3 hours. Recoat time: 3 – 4 hours.</p>		
<b>Coverage</b>	<p>The coverage should be an average of 14m<sup>2</sup> per litre.</p>		
<b>Thinners</b>	<p>Should it be deemed necessary to thin, water should be used up to a level of 10%.</p>		
<b>Equipment Cleaning</b>	<p>Wash brushes/rollers immediately after use, in warm water containing a little detergent.</p>		
<b>Packaging</b>	<p>These products are available in 1 litre, 2.5 litre and 5 litre containers.</p>		
<b>Storage</b>	<p>This product must be protected from frost. Store at temperature above 5°C.</p> <p>Use within 12 months.</p>		
<b>Health and Safety</b>	<p>Refer to Designers Guild MSDS before use.</p>		