

DESIGNERS GUILD

WOOD PRIMER

General	A high quality white water based primer/undercoat for wood which is suitable for interior and exterior use.		
Product Codes	Product Wood Primer and Undercoat	Product code TBC	Sheen n/a
Technical Data	<p>This is a waterbased acrylic primer/undercoat for use on timber and fibreboard substrates.</p> <p>It is suitable for interior and exterior use.</p> <p>The product's speed of dry allows for two coats to be applied in one day.</p> <p>The primer is low odour.</p> <p>It has excellent coverage properties.</p> <p>The primer is available in white only from stock but light and dark grey available on request.</p>		
VOC	Low VOC. EU limit for this product (Cat A/g): 30g/l. This paint contains max 30 gms/l VOC		
Application	<p>Stir well before use.</p> <p>Do not use in extremes of temperature.</p> <p>This product is formulated for brush or roller application.</p>		
Drying Time	<p>Touch dry: 1 – 2 hours.</p> <p>Recoat time: 2 – 4 hours.</p>		
Coverage	Coverage approximately 10-12m ² per litre depending on the nature and porosity of the substrate.		
Thinners	Should it be deemed necessary to thin, water should be used, but exercise care as a little water will thin the primer quickly.		
Equipment Cleaning	Wash brushes/rollers immediately after use, in warm water containing a little detergent.		
Packaging	These products are available in 1 litre, 2.5 litre containers.		
Storage	<p>This product must be protected from frost.</p> <p>Store at temperature above 5°C.</p> <p>Use within 12 months.</p>		
Health and Safety	Refer to Designers Guild MSDS before use.		