

# DESIGNERS GUILD

## FLOOR PAINT

<b>General</b>	A good quality water based paint for use on wooden floors.		
<b>Product Codes</b>	<b>Product</b> Floor Paint	<b>Product code</b> TBC	<b>Sheen</b> 23%
<b>Technical Data</b>	<p>This is a water based alkyd for use on wooden floors.</p> <p>This product is not suitable for use on concrete or cement floors.</p> <p>This product is washable.</p> <p>It is a low odour product with good stain and chemical resistant properties.</p>		
<b>VOC</b>	Low VOC. Eu Limit for this product (Cat A/i): 140g/l. This paint contains max 50gms/l VOC		
<b>Application</b>	<p>Ensure all surfaces are clean, dry and free of contamination. The paint may be thinned up to 10% as a primer coat. Ensure that knots are painted over with a knotting solution.</p> <p>Do not use in extremes of temperature. Use between 8°C to 30°C.</p>		
<b>Drying Time</b>	<p>Touch dry: 1 – 2 hours.</p> <p>Recoat time: 4 hours.</p> <p>Time for light usage: 24 hours. For full cure allow 1 week drying.</p>		
<b>Coverage</b>	The coverage should be an average of 12m <sup>2</sup> per litre.		
<b>Thinners</b>	If required, the paint maybe thinned with up to 10% water .		
<b>Equipment Cleaning</b>	Wash brushes/rollers immediately after use, in warm water containing a little detergent.		
<b>Packaging</b>	This product is available in a 2.5 litre and 5 litre container.		
<b>Storage</b>	<p>This product must be protected from frost.</p> <p>Store at temperature above 5°C.</p> <p>Use within 12 months.</p>		
<b>Health and Safety</b>	Refer to Designers Guild MSDS before use.		