

DESIGNERS GUILD

MASONRY PAINT

General	A good quality water based paint for use over masonry.		
Product Codes	Product Masonry Paint	Product code TBC	Sheen 5%
Technical Data	<p>This is a water based acrylic for use on masonry.</p> <p>This product is not suitable over limewash.</p> <p>This product is also not suitable over lime or lime based renders.</p> <p>This paint is available in white only from stock but may be tinted to a colour on request.</p>		
VOC	Low VOC. EU limit for this product (Cat A/c): 40g/l. This paint contains max 40gms/l VOC.		
Application	<p>Ensure all surfaces are clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with propitiatory sterilisation wash as directed by manufacture.</p> <p>The paint may be thinned up to 10% as a primer coat.</p> <p>If painting over powdery or porous surfaces use stabilising solution.</p> <p>Do not use in extremes of temperature. Use between 8°C to 30°C.</p> <p>Do not apply if there is likelihood of rain.</p>		
Drying Time	<p>Touch dry: 1 – 2 hours.</p> <p>Recoat time: 4 hours.</p>		
Coverage	Up to 15m ² per litre depending on porosity and texture of the substrate.		
Thinners	If required, the paint maybe thinned with up to 10% water .		
Equipment Cleaning	Wash brushes/rollers immediately after use, in warm water containing a little detergent.		
Packaging	This product is available in a 2.5 litre and 5 litre container.		
Storage	<p>This product must be protected from frost.</p> <p>Store at temperature above 5°C.</p> <p>Use within 12 months.</p>		
Health and Safety	Refer to Designers Guild MSDS before use.		