

DESIGNERS GUILD

WALL PRIMER

General	A high opacity, low odour, micro-porous, water thinned wall primer sealer displaying excellent adhesion to most existing finishes. Highly recommended for use under Mylands water based finishes for internal applications. Suitable for preparing new plaster, friable or patch-repaired surfaces, following appropriate preparation.		
Product Codes	Product Wall Primer	Product code	Sheen 6%
Technical Data	This is a water based product to be used on internal walls. This product is not suitable for external walls.. This paint is available in white only and is not a tintable product.		
Application	Ensure all surfaces are clean, dry and free of contamination. The paint may be thinned up to 10% as a primer coat. If painting over powdery or porous surfaces use stabilising solution. Treat algal/fungal contaminated surfaces with dilute bleach or with a proprietary wash, then wash and clean thoroughly to remove all debris. Do not use in extremes of temperature. Use between 8°C to 30°C. Do not apply if there is likelihood of rain.		
Drying Time	Touch dry: 1 – 2 hours. Recoat time: 4 hours.		
Coverage	Up to 15m ² per litre depending on porosity and texture of the substrate.		
Thinners	If required, the paint maybe thinned with up to 10% water .		
Equipment Cleaning	Wash brushes/rollers immediately after use, in warm water containing a little detergent.		
Packaging	This product is available in a 5 litre container.		
Storage	This product must be protected from frost. Store at temperature above 5°C. Use within 12 months.		
Health and Safety	Refer to Designers Guild MSDS before use.		